

ETHERLINE® 4 pair: CAT.6A; continuous flex

Industrial Ethernet cable for continuous flex applications



This ETHERLINE® 4 pair cable meets CAT.6A requirements and is suitable for continuous flex applications. Individually shielded pairs and an overall braid shield protect the cable from EMI and allow reliable, high-speed data transfer. The cable is available with a PVC or halogen-free polyurethane jacket.

Construction

- Conductors:** stranded tinned copper
- Pairs:** 4 pairs individually shielded with aluminum compound foil
- Insulation:** foam skin
- Shielding:** overall copper braid
- Jacket:** PVC or polyurethane; green

Recommended applications

Continuous flex applications; cable tracks; moving machine parts; harsh environments; qualified for CAT.6A = 10 Gbits/s

Approvals



Application advantage

- Suitable for EtherCAT® & EtherNet/IP applications
- Qualified for 10 Gigabit Ethernet
- Premium shielding against EMI
- Oil-resistant jacket
- Conforms to PROFINET® standard
- Suitable for PoE per IEEE 802.3at

Cable attributes page 648

See attribute list by part number on page 234 *

Complete the installation



SKINTOP® MS-SC
page 522



RJ45 CAT.6A
connectors
page 258

ÖLFLEX® CONNECT solution



Industrial Ethernet cordsets
page 620

Technical data

<p>Minimum bend radius: - for continuous flexing: 15 x cable diameter</p> <p>Temperature range: - for stationary use: -40°C to +80°C - for continuous flexing: -10°C to +70°C</p> <p>Nominal voltage: (not for power applications) - 2170484: 1000V - 2170485: 125V</p> <p>Characteristic impedance: 100Ω ± 15Ω</p>	<p>Color code: white & blue, white & orange, white & green, white & brown</p> <p>Approvals: UL: AWM 21576 (2170484) CMX per UL 444 (2170484) RU AWM 80°C 1000V (2170484) CMG per UL 444 (2170485) Canada: c(UL) CMX (2170484) cRU AWM I/II A/B FT2 (2170484) c(UL) CMG FT4 (2170485) Additional: RoHS *UL Verified ID A522492: Continuous Flex Test Method Verified</p>
---	--

Part number	Construction	Stranding	Jacket material	Jacket color	Approvals	Fast connect	PoE	Nominal outer diameter in	Nominal outer diameter mm	Approx. weight lbs/mft	SKINTOP® MS-SC PG thread
CAT.6A											
2170484	24 AWG/4pr	7 wire	PUR	green	PROFINET®, UL/CSA AWM, CMX	no	yes	0.355	9.0	60	53112220
2170485	24 AWG/4pr	7 wire	PVC	green	PROFINET®, UL/CSA CMG	no	yes	0.355	9.0	59	53112220

PROFINET® is a registered trademark of the PNO (PROFIBUS User Organization). EtherCAT® is a registered trademark of Beckhoff Automation GmbH. Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section. If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question.