

DON'T GAMBLE WITH YOUR TIME & MONEY!

THE NFPA 79 ELECTRICAL CODE HAS CHANGED.



**THE LAPP GROUP HAS
ALL YOUR BETS COVERED.**

**SELECTING THE RIGHT CABLE FROM THE LAPP GROUP IS THE
SAFEST BET YOU CAN EVER MAKE.**

Lapp Group offers a variety of cables that help you follow the code, call or visit our website to download our NFPA Cable Brochure.

(<http://www.lappusa.com/Applications-NFPAWhitePaper.htm>)

800-774-3539

www.lappusa.com • www.lappcanada.com



LAPP GROUP

Lapp UL Listed Products Conforming to NFPA 79 2007

PRODUCT	APPLICATION	KEY FEATURES
OLFLEX® TRAY II: Shielded & Unshielded 	Stationary Control	Tray rated for extended runs, no need for conduit. Highly flexible for ease of installation, save time and money, highly oil and chemical resistant. MTW all sizes
Compliant Status: Always		
OLFLEX® TC 600 	Stationary Control	Contractor grade tray cable with UL TC-ER approval, no need for conduit. MTW sizes 14 AWG and larger
Compliant Status: 14 AWG & Larger- Always		
OLFLEX® CONTROL TM 	Stationary Control	Flexible and oil resistant tray and machine cable. MTW all sizes
Compliant Status: Always		
OLFLEX® CONTROL M 	Stationary Control	Flexible and oil resistant MTW cable for PUR jacketed alternative. MTW all sizes
Compliant Status: Always		
OLFLEX® FORTIS 	Stationary Control	Flexible at -40°C and Oil Res I & II, suitable for tray, machine, and cold temperature applications.
Compliant Status: Always		
OLFLEX® 190: Shielded & Unshielded 	Stationary Control	All advantages of 190 cable plus MTW rating
Compliant Status: Production Since 2/23/07		
OLFLEX® Auto I 	Stationary Control	Available in blue and red conductors to differentiate DC and AC control circuits. MTW sizes 16 & 18 AWG
Compliant Status: Always		
OLFLEX® CHAIN 879: Shielded & Unshielded 	Continuous Flex Control	Designed for continuous flex cable tracks or chains, meets Oil Res I/II for long service life.
Compliant Status: Always		
OLFLEX® Auto X 	Continuous Flex Control	Designed for continuous flex cable tracks or chains, highly oil and chemical resistant. MTW sizes 18 & 16 AWG
Compliant Status: Always		
OLFLEX® VFD Slim 	Stationary VFD Cable	Reduced diameter, flexible VFD cable with "Lapp Surge Guard" with UL and CSA TC approval. MTW all sizes
Compliant Status: Production as of 4/1/07		
OLFLEX® VFD 	Stationary VFD Cable	Oil resistant 1000V VFD cable with Bus Drop approval MTW sizes 14 AWG to 2 AWG
Compliant Status: Production as of 4/1/07		
OLFLEX® with Signal 	Stationary VFD Cable	Oil resistant VFD Cable with a shielded pair for a brake or for temperature control.
Compliant Status: Production as of 4/1/07		
OLFLEX® SDP TC 	Motor Supply Power and BUS Cable	Stationary severe duty power cable with specially formulated oil and chemical resistant elastomeric alloy jacket
Compliant Status: Production as of May 1, 2007		