

Striping, Dyeing & Twisting

Custom Fabrication Capabilities

UL & CSA Approved

The Lapp Group has the ability to do custom fabrication to single core wire such as striping, dyeing, twisting and even printing. We have UL & CSA approval to respool & repack the wire to meet your custom lengths (max OD: .750). The standard minimum is 1000 ft.

Below is a chart giving the details of our capabilities based on the single core wire offered in this section of the catalog.

Spiral Striping:

- 28 AWG to 10 AWG up to 3 stripes
- 1000 ft minimum
- Ability to identify the wire for easier installation
- Quick turn around time

Twisting:

- 30 AWG to 10 AWG up to 4 wires
- 1000 ft minimum
- Ability to twist per spec
- Quick turn around time

Dyeing:

- 28 AWG to 10 AWG
- 1000 ft minimum
- PVC Insulation
- Quick turn around time

Printing

- 22 AWG to 10 AWG
- Print wheels are made to order
- 1000 ft minimum



Wire Type	PVC 1015, 1028, 1283, 1007, 1061	XLP GXL, SXL, TXL	Teflon® Wire
Stripe (spiral) 1000 ft min	28 AWG to 10 AWG up to 3 stripes	28 AWG to 10 AWG up to 3 stripes	28 AWG to 10 AWG up to 3 stripes
Twist 1000 ft min	30 AWG to 10 AWG up to 4 cond.	30 AWG to 10 AWG up to 4 cond.	30 AWG to 10 AWG up to 4 cond.
Dye Wire 1000 ft min	Up to 10 AWG	-	-
Print 1000 ft min	Made to order wheels 22 AWG to 10 AWG	Made to order wheels 22 AWG to 10 AWG	Made to order wheels 22 AWG to 10 AWG

Teflon® is a registered trademark of DuPont.