

EPIC® Connector Accessories

Split Hoods

DOUBLE LATCH BOLTS SPLIT HOODS FOR HBE 16 & 24

Split hoods allow multiple cable assemblies to pass through one hood.

Split hoods provide a convenient way to pass finished cable assemblies through a connector housing into a panel without having to reterminate the assembly. A maximum of 4 cables ranging in size from 3 mm to 16 mm each may pass through a single hood.



Part #	Description	Wire Range	Mates with Panel Mount Base
HBSH16	3 gland openings	3 mm - 16 mm	10072000
HBSH24	4 gland openings	3 mm - 16mm	10102000

The part numbers listed are for a complete hood (two halves).

Both the 16 position and 24 position versions can accommodate any combination of the grommets listed below. When used with these grommets, the split hood will provide an IP 54 environmental seal.

SPLIT GROMMETS

Thermoplastic rubber split grommets are available in a range of sizes. The grommets seal around the cables and provide IP 54 protection rating as well as strain relief in the mated and assembled position. The HBSH 16 Housing is capable of accommodating 3 glands. The HBSH 24 Housing can accommodate 4 glands.



Part #:	Clamp Range:	Standard Pack
SHG 3	3 - 4mm	10
SHG 4	4 - 5 mm	10
SHG 5	5 - 6 mm	10
SHG 6	6 - 7 mm	10
SHG 7	7 - 8 mm	10
SHG 8	8 - 9 mm	10
SHG 9	9 - 10 mm	10
SHG 10	10 - 11 mm	10
SHG 11	11 - 12 mm	10
SHG 12	12 - 13 mm	10
SHG 13	13 - 14 mm	10
SHG 14	14 - 15 mm	10
SHG 15	15 - 16 mm	10
SHG 0	0 (blank)	10
SHG ASI	ASI Cable	10

Material: Thermoplastic rubber (UL Approved)

Temperature: -40°C to +140°C