

SKINDICHT® SKZ/ SKZ-M Series




Compact Strain Relief Cable Gland with Double Saddle Clamp with Additional Sealing in PG & Metric Threads

The SKINDICHT® SKZ cable clamp is a compact strain relief cable gland with double saddle clamps and additional sealing. The sealing is achieved by means of a multi-layered bushing that accommodates a large cable diameter range.

Application Advantage:

- The extended fitting allows the clamp to reach protection class IP55
- An o-ring is included on the mounting thread to provide additional sealing



Technical Data:



Materials:
 Body: Nickel-Plated Brass
 Saddle Clamp: Nickel-Plated Brass
 Screws: Nickel-Plated Brass
 Bushing: Neoprene
 Sealing O-ring: Perbunan (NBR)
 Incised Sealing Ring:
 - SKZ: CR
 - SKZ-M: CR (NBR)



Temperature: -20° C to +80° C



Seal: IP 55

Locknuts: Add SM Locknuts, see Page 522

SKINDICHT® SKZ: Compact Strain Relief Cable Gland with PG Threads

Part Number	Thread Type & Size	Clamping Range øF inches	SW 1/2 Wrenching Flats inches	C Overall Length inches	D Thread Length inches	Max. Installation Diameter inches	Standard Pack Size
52004280	PG-9	.236 - 0.335	.67/.67	1.181	.236	0.945	50
52004290	PG-11	.315 - 0.472	.79/.83	1.181	.236	1.063	50
52004300	PG-13	.472 - 0.551	.87/.87	1.339	.256	1.181	25
52004310	PG-16	.512 - 0.630	.94/.94	1.378	.256	1.299	25
52004320	PG-21	.591 - 0.827	1.18/1.18	1.614	.276	1.654	25
52005570	PG-29	.787 - 1.083	1.57/1.61	1.811	.315	2.283	10

SKINDICHT® SKZ-M: Compact Strain Relief Cable Gland with Metric Threads

Part Number	Thread Type & Size	Inner Thread	Clamping Range øF inches	SW 1/2 Wrenching Flats inches	C Overall Length inches	D Thread Length inches	Max. Installation Diameter inches	Standard Pack Size
52106800	M-16X1.5	PG-9	.197 - 0.315	.71/.67	1.142	.197	0.945	50
52106810	M-20X1.5	PG-11	.276 - 0.472	.87/.79	1.181	.236	1.063	50
52106820	M-20X1.5	PG-13	.433 - 0.512	.87/.87	1.319	.236	1.181	25
52106830	M-20X1.5	PG-16	.512 - 0.591	.94/.94	1.358	.236	1.299	25
52106840	M-25X1.5	PG-21	.630 - 0.760	1.18/1.18	1.614	.276	1.654	25
52106850	M-32X1.5	PG-29	.748 - 1.063	1.57/1.61	1.811	.315	2.283	10