

SILVYN® AS Conduit

Flexible Steel Reinforced Metal Conduit



SILVYN® AS is designed with an interlocking spirally wound metal armor.

Application Advantages:

- Highly resistant to pressure, impact and mechanical stress, while providing superior flexing qualities
- Ideal for heavy mechanical stress



SILVYN®
US
See Page 592



SILVYN®
US MS-DR
See Page 593

Technical Data:



Materials: Galvanized Steel



Color: Gray



Temperature range: up to +220°C



Protection: IP 40

SILVYN® AS Conduit: Steel Reinforced Metal Conduit

Part Number	Outer Diameter		Inner Diameter		Bend Radius		Conduit Coil Put-Ups Feet	Thread Type & Size for Fittings	
	inches	mm	inches	mm	inches	mm		PG	Metric
61802080	.394	10	.315	8	1.102	28	164	PG-7	M-10X1.5
61802090	.551	14	.433	11	1.339	34	164	PG-9	M-12X1.5
61802100	.669	17	.551	14	1.575	40	164	PG-11	M-16X1.5
61802110	.748	19	.630	16	1.772	45	164	PG-13	---
61802120	.827	21	.709	18	1.969	50	164	PG-16	M-20X1.5
61802130	1.063	27	.906	23	2.480	63	164	PG-21	M-25X1.5
61802140	1.417	36	1.220	31	3.346	85	82	PG-29	M-32X1.5
61802150	1.772	45	1.575	40	3.937	100	82	PG-36	M-40X1.5
61802170	2.205	56	2.008	51	4.921	125	82	PG-48	M-50X1.5

* Fittings available in PG and Metric, see SILVYN® US on page 592 and SILVYN® US MS-DR on page 593.